

DC930&DC940 Small Character Inkjet Printer



- Features:
- ◆Printing speed, high speed up to 410 m/min
 - ◆Printing Chinese characters up to 220 m/min
 - ◆Multi nozzle: 70u, 55u, 42u nozzle
 - ◆Various ink colors: black, white, blue, red, etc
 - ◆Easy to maintain
 - ◆Online editing
 - ◆Widely used in food, beverage, chemical, cable pipe and other industries.

Simple

Simple ink system design,
convenient daily use and
maintenance.

Reliable

Stable and reliable ink system,
safe and efficient.

Economical

Use and maintenance at ease,
cost-effective choice.

Print Results:



Official Website



WhatsApp

SHANGHAI DIKAI CODING TECHNOLOGY CO.,LTD

Add: 6F, No.2 Building, 32# Wudong Rd, Haida Industry Zone,
Shanghai 200433, PRC
Tel: +86 13764900450
www.dkcoding.net Email: info@dkcoding.net

Features:

Printing specifications	Production date, expiration date, lot number, graphics, logo, count, time, date, shift, etc DC930:1 to 5 lines (32 dots); DC940:1 to 8 lines (48 dots) Printing speed:410m/min (5*5, single line) Direct input simplified Chinese, traditional Chinese, English, Arabic, Persian, support vector fonts
Interfaces	10.1-inch touch screen Universal USD interface, plug and play, easy backup and restore printed text and configuration Ethernet communication interface (10~100MB) Supports RS232-485 communication Security code, variable barcode printing, QR code, etc
Software function	Android control system, easy to use, stable and reliable. Multi-language software interface, easy to switch User friendly interface-WYSIWYG. Built-in full-screen graphics editor, easy to edit graphics and logo 8GB memory storage space; Upgrade software over Ethernet. Pop-up periodic device maintenance reminder RUN/STOP hotkeys automatically switch on and off the machine Real-time date and time display Preset standard and multi-line high speed print mode to meet different user needs A variety of text formats: mirror flip, up and down flip, anti-white, bold, double point spacing and so on Text can add up to 3 counters and 4 shifts OPS synchronous printing reverse compensation function DMS automatically calculates the meter pulse Multi-level passwords assign different permissions to different users
Types of ink	Full range of ink, pigment and dye inks, multi colors. The specific type and parameters shall be subject to the sampling test
Certification	TUV-ISO9001 quality system CE(EMC,MD&LVD)
Appearance parameter	Stainless steel case, IP54 protection rate Standard umbilical:20 mm in diameter, 2.5 m in length Cabinet dimensions: height 576 mm x width 360 mm x depth 328 mm Nozzle dimensions:210 mm * 45 mm * 50 mm Net weight:27 kg Power input:110~220V, 50/60Hz; Multi-specification power plug is optional
Environment	Temperature:4~45°C (35~100°F) Humidity: maximum 90%, no condensation
Optional accessories	Photoelectric eye sensor, encoder Tri-color alarm light Print head bracket, meter counting holder for cable Solvent condensate recovery device, nozzle positive air pressure pump Adjustable speed conveyor belt

Size:
